

# WALL MOUNT FLANGE DISCONNECT ENCLOSURE TYPE 12

## CONSTRUCTION DETAILS

- ) 14 gauge steel
- ) Seams continuously welded and ground smooth
- ) External welded on mounting brackets
- ) Screw style door clamps on three sides to secure the door
- ) Padlock feature on door
- ) Continuous hinge with removable hinge pin
- ) Collar studs for mounting optional rear sub panel
- ) Bonding stud on door
- ) Print pocket on door
- ) Interlock bracket for attaching disconnect door catch
- ) Closed cell oil resistant neoprene gasket

*\*Custom is what we do. Contact our sales office for a quote on custom enclosure features.*

## FINISH

- ) IEC-Line Gray powder coated inside and out<sup>1</sup>
- ) Optional sub panel painted RAL 9003 white<sup>2</sup>

<sup>1</sup> Finish with a standard RAL powder color inside and out of your choice at no additional cost

<sup>2</sup>Galvanized sub panel available; mill finish

## INDUSTRY STANDARDS

- ) Nema Type 12 and 13
- ) UL Listed Type 12 and 13
- ) CSA Type 12
- ) IEC 60529 IP65

## ADDITIONAL AVAILABLE MODELS

- ) Single Door Flange Disconnect With Three Point Handle

IEC FILE REFERENCE: N12\_1D\_WM\_FMD

